John Lewis Uncorded Curtain Track

Thank you for purchasing this product from John Lewis. Please read the instructions and warnings carefully before use to ensure safe and satisfactory operation of this product.

Suitable for straight runs and bay windows.

Recommended maximum curtain weight is 13.6kg (30lb)

I. Pack Contents

Track size	I50cm	200cm	250cm
Brackets	6	8	9
End stops	2	2	2
Gliders	20	28	32

This pack contains everything you need to install this track to a pre-installed batten.

Note: When mounting to a masonry, dry line wall, stud wall or ceiling, please ensure the correct drill bit, screws and fixings are used.

You will require the following tools: pencil, electric drill, hammer, screwdriver, measure, spirit level. If fixing to plaster or masonry, medium size wall plugs suitable for No. 6, 8 and 10 screws will be needed.

2. Positioning the Brackets



a. For straight runs

Mark a straight line along the wall or ceiling equal to the finished track length required.


Mark the end bracket positions 6.5cm ($2\frac{1}{2}$ in) in from the end of the line. Mark equally spaced positions for all remaining brackets.


b. For bay windows


Right-angle bay: approx bracket positioning 24cm (91/2") max radius 20cm (8")

Three-sided bay: approx bracket positioning 20cm (8")

Five-sided bay: approx bracket positioning 10cm (4")







3. Fixing the Brackets

Fix the backplates in position as directed above (fig 1).

Slide the faceplates onto the track to match the position of the backplates (fig 2).

Secure end stops in position.

Locate the faceplate into the backplate and snap into place.

fig I.





Shortening track

a. For straight runs

To be cut from one end only. Remove end stop and mark the cut line on the track. Cut using a sharp hacksaw and replace the end stop.

b. For bay windows

The track must be temporarily installed and measured in position to ensure accurate shortening.

Starting at one end, present the back of the track to the first fixing bracket. Allow 6.5cm ($2^{1/2}$ ") of track to project at the end and, maintaining the required shape through the bay fit the track to each bracket in turn. Allow 6.5cm ($2^{1/2}$ ") overhang on the last bracket and mark the cut position.

Release the track from the brackets and cut square at the mark using a sharp hacksaw. Replace the end stops.

Note: always remove sharp edges


Hanging curtains

The maximum recommended curtain weight is 13.6kg (30lb).

Insert glider hooks into curtain tape at equal intervals.

Clip glider hooks onto track.

If using curtain hooks, clip gliders onto track and insert hooks into eyes.



Care and maintenance

Your John Lewis uncorded curtain track may be cleaned by wiping the rail and fittings with soapy water. When dry, apply a siliconebased polish to the running surfaces to ensure smooth operation.

Warning

It is recommended that this product should only be installed by persons competent in DIY. Ensure the correct fixings are used for the appropriate wall type. If in doubt, consult a qualified person.