Product Information Sheet (EU Regulation 2019/2013)							
	Parameter	Parameter		Value	and Precision	Unit	
1	Supplier's name or trade mark		Panasonic Corporation				
	Supplier's address		Panasonic Testing Centre Panasonic Marketing Europe GmbH Winsbergring 15, 22525 Hamburg, Germany		ing Centre g Europe GmbH		
2	el identifier		TX-50MX600B		500B		
3	y efficiency class for Standard Dynamic Range (SDR)		F				
4	ode power demand for Standard Dynamic Range (SDR)		65.0			W	
5	gy efficiency class (HDR)		G				
6	ode power demand in High Dynamic Range (HDR) mode, if implemented		110			W	
	oode, power demand, if applicable		0.3			w	
	by mode power demand, if applicable		0.5			W	
9 10	Networked Standby mode power demand, if applicable	Television	2.0 vision			W	
		Monitor					
	Electronic display category	Signage					
		Other					
11	Size ratio		16	1	9	integer	
	Screen resolution (pixels)		3840	x	2160	pixels	
	Screen diagonal			125.7		cm	
14	Screen diagonal		1	50		inches	
	Visible screen area		67.5			dm ²	
	Panel technology used		DIRECT LED		FD	um	
17		YES	Sincer LED				
1/	Automatic Brightness Control (ABC) available	NO					
18	Voice recoganition sensor available	YES					
19		NO YES					
	Room presence sensor available	NO					
20	Image refresh frequency rate (default)		50			Hz	
21	Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market)	8			Year		
22	Minimum guaranteed availability of spare parts from the date of end of the placement on the market)	7			Year		
23	imum guaranteed product support		7			Year	
	Minimum duration of the general guarantee offered by the supplier		1			Year	
24		Internal					
	Power supply type	External					
		Standardised external					
25	ernal power supply (non standardized and included in the product box)						
i							
ii		Input Voltage				V	
		Output Voltage				v	
26	6 External standardised power supply (or suitable one if not included in the product box)						
i		Standard Name or list					
ii		Required output voltage				v	
		Required delivered current				А	
iv		Required current frequency				Hz	