



VINTAGE GLOBE OUTDOOR IP44 FLUSH LIGHT

USER GUIDE



Introduction

Thank you for purchasing this Vintage
Globe outdoor IP44 flush wall light.
Please read the instructions carefully
before use to ensure safe and satisfactory
operation of this product.

Warnings



We recommend a qualified electrician carries out any electrical wiring outdoor. For your safety, this product must be installed in accordance with local Building Regulations.

If in any doubt, or where required by the law, consult a competent person who is registered with an electrical self-certification scheme. Further information is available online or phone your Local Authority.

To prevent electric shock, switch off the mains supply before installing or maintaining this product. Ensure other persons cannot restore the electricity supply without your knowledge.

Always use the correct bulb type with the correct wattage as indicated in the specification table. This product is Class I = \equiv and should be fitted to a lighting supply (with earth) protected by a 5 amp fuse or equivalent circuit breaker.

When changing the bulb, always switch off at the mains and allow the old bulb to cool down before handling. Dispose of used bulbs carefully.

Caution! The bulb and surrounding parts can become hot during use.

If the inner glass on this product is broken, it must be replaced


Parts list

	Description	Image	Quantity
A	Wall Light		1
B	Shade glass		1
C	Wall cup/ fixing bracket		1
D	Fixing screw pack		1

Product assembly

1


C D



Remove mounting cup/bracket (C) from fitting by removing the retaining screws and washers, retain for later. Using the mounting bracket as a template, mark and then drill the fixing holes in the wall (ensure the screws (D) are firmly fixed into a solid or other suitable mounting and not just the plasterboard.). Take care not to damage wiring. Pierce a hole in the rubber cable grommet at the rear of the wall cup and carefully feed the household supply cable through. Attach mounting cup to the wall using suitable fixings.

2

A




Lever open the terminal block box cover with a screwdriver, pierce a hole in the black rubber end cap of the terminal block then feed supply cable through. Make electrical connections as follows:

- Connect supply live to fitting live (marked "L") on the terminal block.
- Connect supply neutral to fitting neutral (marked "N") on the terminal block.
- Connect the supply earth to the earth (marked " \perp ") on the terminal block.

NOTE: Ensure electrical connections are tight and no loose strands of wire are left out of the connector block. Ensure terminals and rubber sleeve are correctly seated then close connector block housing. Excess cable must be carefully located inside ceiling cup or within the ceiling void. Excess cable must be carefully located inside the wall plate or within the wall cavity itself. Carefully offer fitting (A) over mounting bracket then secure in place with the screws and washers removed earlier.

3

B



Fit the bulb, type and wattage as indicated on the fitting (bulb not supplied). The wattage indicated must not be exceeded.

To fit the shade (B): Offer the shade glass over the lamp holder section, align the treads and carefully screw into place. If cross-threading occurs, undo and start again. Take care not to over-tighten as this may cause damage to the the glass or the fitting. Once installation is complete, the electricity may be restored at the fuse box.

**Caring for
your product**

We recommend cleaning with a soft dry cloth. Do not use abrasive materials as these will damage the finish.
Replace bulb from John Lewis or established brand of the same type and compatibility.

**Aftercare and
Troubleshooting**

If you experience any unresolvable technical issues with the product, contact your nearest John Lewis & Partners shop or John Lewis & Partner Technical Support on 03301 230106.

Why is the light not working when switched on?
Check your power supply is switched on
Turn off light and check that the bulb is inserted correctly
Check the bulb is still in working order.

Specification

Max. power: 5W LED Only (500-700 lumen)
Voltage: 220–240V, 50Hz IP rating: 44
Weight: 0.8kg



5 year guarantee

At John Lewis & Partners we test every light to high quality standards so we are able to offer you a 5 year guarantee.

Recycling

This symbol  indicates that this product should not be treated as normal household waste and it should be recycled. John Lewis & Partners do not operate instore take back, but as members of the Distributor Take Back scheme have funded the development and upgrade of recycling facilities across the UK. Please take it to your nearest collection facility or for further details contact your local council or visit www.recycle-more.co.uk.



John Lewis Partnership
171 Victoria Street
London SW1E 5NN
johnlewis.com

Made in China

Please retain these instructions for future reference.
