## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Model	identifier	9290030186
IVICICIEI	meniner:	9/90050160

_	•			
IVna	Λt	light	source	٠.
IVDC	vı	HEILL	Jource	- •

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

## **Product parameters**

				7
Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded est integer	7	Energy efficiency class	Е
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode power (Pon), expressed in W  Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal		7,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50
		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	143	Spectral power	See image
dimensions	Width	64	distribution in the	in last page
				Page 1 / 2

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	64	range 250 nm to 800 nm, at full-load		
Claim of equival	Claim of equivalent power <sup>(a)</sup>		If yes, equivalent power (W)	60	
			Chromaticity coordinates (x and y)	0,312	
Parameters for I	LED and OLED lig	ht sources:			
R9 colour rende	ring index value	0	Survival factor	0,90	
the lumen main	the lumen maintenance factor				
Parameters for I	Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that a source replaces light source with ballast of a parti	hout integrated	_(b)	If yes then replacement claim (W)	-	
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,9	

(a)'-': not applicable; (b)'-': not applicable;

