## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	PHILIPS
--------------------------------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL
--------------------------------------------------------------------------------------------------

Model identifier: 9	290030176
---------------------	-----------

_	•			
Tyna	At.	liaht	source	٥.
IVDC	OI.	IIGIIL	Souic	឴

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

## **Product parameters**

Froduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consur mode (kWh/10 up to the neares	00 h), rounded	5	Energy efficiency class	F
indicating if it re	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode pexpressed in W	oower (P <sub>on</sub> ),	4,9	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50
Networked stan for CLS, expres rounded to the		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	113	Spectral power	See image
dimensions	Width	35	distribution in the	in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	35	range 250 nm to 800 nm, at full-load	
Claim of equivale	nt power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	50
			Chromaticity coordinates (x and y)	0,312
Parameters for LI	ED and OLED lig	ht sources:		
R9 colour renderi	ing index value	0	Survival factor	0,90
the lumen mainte	enance factor	0,93		
Parameters for LI	ED and OLED ma	ains light sources:		
displacement fac	tor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that a source replaces light source with ballast of a partic	a fluorescent out integrated	_(b)	If yes then replacement claim (W)	-
Flicker metric (Ps	t LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

