## JOHN LEWIS

## & PARTNERS

**Product Information Sheet** 

Supplier's name or trade mark:			John Lewis			
Supplier's address (°):			John Lewis & Partners 171 Victoria Street, London, SW1E 5NN JLCABFR185			
Low-noise appliance:		no	Design type:		freestanding	
Wine storage appliance:		no	Other refrigerating a	no		
General product p	parameters:					
Parameter		Value	Parameter		Value	
	Height	1860				
Overall dimensions (millimetre)	Width	595	Total volume (dm <sup>3</sup> or I)		389	
(	Depth	650				
EEI		99	Energy efficiency cla	ss	E ( <sup>C</sup> )	
Airborne acoustical noise emissions (dB (A) re 1 pW)		40	Airborne acoustical noise emission class		c ( <sup>c</sup> )	
Annual energy consumption (kWh/a)		121.00	Climate class:		extended temperate / temperate / subtropical / tropical	
Minimum ambient temperature (°C), for which the refrigerating appliance is suitable		10 ( <sup>C</sup> )	Maximum ambient temperature (°C), for which the refrigerating appliance is suitable		43 ( <sup>C</sup> )	
Winter setting		no				
Compartment Par	rameters:					
		Compartment parameters and values				
Compartment typ	e	Compartment Volume (dm <sup>3</sup> or l)	Recommended temperature setting for optimised food storage (°C) These settings shall not contradict the storage conditions set out in Annex IV, Table 3	Freezing capacity (kg /24 h)	Defrosting type (auto-defrost = A, manual defrost = M)	
Pantry	no	-		-		
			1			

Wine storage	no	-		-		
Cellar	no	-		-		
Fresh food	yes	389.5	4	-	А	
Chill	no	-		-		
O-star or ice- making	no	-		-		
L-star	no	-		-		
2-star	no	-		-		
3-star	no	-		-		
1-star	no	-	-18	-		
2-star section	no	-		-		
/ariable emperature compartment		-			-	
or 4-star compartn	nents					
Fast freeze facility			no			
ight source parame	eters (a) (b):					
Type of light source			[Lighting technology used:LED;Non-directional or directional: NDLS;Mains or non-mains:NMLS;Connected light source (CLS):no;Colour-tuneable light source:no;Envelope:no;High luminance light source:no;Anti-glare shield:no;Dimmable:no]			
Energy efficiency class			F			
Minimum duration	of the guarantee off	ered by the manufac	turer ( <sup>b</sup> ):	36 months		
Additional informati	ion:	-				